

# Powermate®



- 1** Powerful Powermate OHV engine provides consistent power for multiple applications
- 2** Fuel gauge allows user to keep track of gasoline levels
- 3** Includes digital multi meter to record engine run time for scheduled maintenance intervals & AVR (Automatic Voltage Regulator) to keep equipment protected from voltage surges
- 4** Never-Flat wheels allow for easy transportation (included with portability kit)
- 5** Outlet Cover Protection to keep debris out
- 6** Dual folding handles for easier mobility
- 7** Manual/Electric start (battery included with 6500 & 8000)



## Manual Start



Model No.	PM0141200
Rated Watts	1200
Surge Watts	1500
Engine Displacement	98 cc
Low Oil Shutdown	Yes
Fuel Tank Capacity	1.5 Gallons
Fuel Gauge	Yes
Run Time @ 50% Load	10 hours
Starting Function	Manual
Outlets	(1) 5-20R 120V 20A Duplex & 12V DC
Assembled Dimensions	19.8" x 15.6" x 15.9"
Dry Weight	60 lbs.
EAN	8018539072735

Ⓜ(1) 5-20R 120V 20A Duplex Ⓜ 12V DC

## Manual Start



Model No.	PM0143250
Rated Watts	3250
Surge Watts	4050
Engine Displacement	208 cc
Low Oil Shutdown	Yes
Fuel Tank Capacity	4.5 Gallons
Fuel Gauge	Yes
Run Time @ 50% Load	12.2 hours
Starting Function	Manual
Outlets	(2) 5-20R 120V 20A Duplex & L5-30R 120V 30A Twistlock *Includes L5-30P to TT-30R Adapter
Assembled Dimensions	26.7" L x 25.5" W x 20.6" H
Dry Weight	107 lbs.
EAN	8018539072742

Ⓜ(2) 5-20R 120V 20A Duplex Ⓜ L5-30P 120V 30A Twistlock

## Manual Start



Model No.	PM0145500
Rated Watts	5500
Surge Watts	6875
Engine Displacement	420 cc
Low Oil Shutdown	Yes
Fuel Tank Capacity	7 Gallons
Fuel Gauge	Yes
Run Time @ 50% Load	11 hours
Starting Function	Manual
Outlets	(2) 5-20R 120V 20A Duplex & L14-30R 120/240V 30A Twistlock
Assembled Dimensions	31.5" L x 27.3" W x 24.5" H
Dry Weight	173 lbs.
EAN	8018539072889

Ⓜ(2) 5-20R 120V 20A Duplex Ⓜ L14-30R 120/240V 30A Twistlock

## Manual/Electric Start



Model No.	PM0146500
Rated Watts	6500
Surge Watts	8125
Engine Displacement	420 cc
Low Oil Shutdown	Yes
Fuel Tank Capacity	7 Gallons
Fuel Gauge	Yes
Run Time @ 50% Load	9.7 hours
Starting Function	Manual/Electric
Outlets	(2) 5-20R 120V 20A Duplex & L14-30R 120/240V 30A Twistlock
Assembled Dimensions	31.5" L x 27.3" W x 24.5" H
Dry Weight	202 lbs.
EAN	8018539072896

Ⓜ(2) 5-20R 120V 20A Duplex Ⓜ L14-30R 120/240V 30A Twistlock

## Manual/Electric Start



Model No.	PM0148000
Rated Watts	8000
Surge Watts	10000
Engine Displacement	445 cc
Low Oil Shutdown	Yes
Fuel Tank Capacity	7 Gallons
Fuel Gauge	Yes
Run Time @ 50% Load	9.4 hours
Starting Function	Manual/Electric
Outlets	(2) 5-20R 120V 20A Duplex, L5-30R 120V 30A Twistlock & L14-30R 120V/240V 30A Twistlock
Assembled Dimensions	31.5" L x 27.3" W x 24.5" H
Dry Weight	212 lbs.
EAN	8018539072902

Ⓜ(2) 5-20R 120V 20A Duplex Ⓜ L5-30R 120V 30A Twistlock Ⓜ L14-30R 120/240V 30A Twistlock